

technical information

TANTRUM

<p>CHARACTERISTICS</p>	<p>Tantrum is made from a stoneware body. The glass has been encapsulated and fused to the clay.</p>
<p>INSTALLATION & MAINTENANCE</p>	<ul style="list-style-type: none"> - It is very important to use a thin diamond blade to cut Tantrum tiles, not a tile/brick blade. - Use Crazy Glue on cut line to help hold in glass freed from cut. - After installation, surrounding grout will hold glass on cut edges. - Seal tile prior to grouting with a sealer or grout release. This will ease the clean-up process at time of grouting. - It is very important to immediately and continually clean excess grout from the surface as work progresses. Rinse thoroughly with clean water, changing water frequently.
<p>USAGE</p>	<ul style="list-style-type: none"> - Suitable for wall use, both interior and exterior applications. According to ASTM tests may be used in areas that experience freeze-thaw conditions. - Suitable for pools, except in freeze-thaw areas.
<p>ASTM TEST RESULTS (American Society Testing for Materials)</p>	<p>Tantrum tiles were tested by Tile Council of America with the following results: 1) ASTM Test C650: resistant to common household cleaning chemicals and pool chemicals. Best to avoid strong solution acids. 2) ASTM Test C1026: no visible evidence of freeze-thaw damage.</p>